

## COATING THICKNESS GAUGE IPX-201F™

Handheld coating thickness gauge with F-probe for steel substrates

- Clear 4 digit segment LCD display
- Magnetic induction measuring principle
- Non-magnetic coating on ferrous substrates
- Easy calibration



### Technical specifications

Principle	Magnetic induction
Application	Non-magnetic coating on ferrous substrates
Display	4 digit segment LCD
Measuring range	0 - 1000 µm with standard probe (15000µm max/600mil max)
Resolution	0 - 99.9µm, 0.1µm 100-1.000µm, 1µm
Accuracy (n = nominal value)	± (1~3%n) or ±2.5µm
Measuring unit	µm/mil
Standard	ISO
Sample	
Min. radius workpiece	Convex 1.5mm Concave 20mm
Min. measuring area	6mm
Min. sample thickness	0.3mm
Battery indicator	Low battery voltage indicator
Operating temperature	0 - 50°C
Power supply	9V 6F22 battery (1 pc)
Dimensions	140mm x 71mm x 32mm
Weight	260gr incl. batteries

### Standard delivery

- Main unit
- F-probe
- Calibration foil set
- Substrate block (iron)
- Carrying case
- Manual
- INSPEX certificate

### Optional accessories

- INSPEX calibration foils in various thickness
- UKAS calibration foils in various thickness
- Measuring range:  
0-200µm / 0-8mil  
0-500µm / 0-20mil  
0-2000µm/0-80mil  
0 up to 15000µm / 600mil with different probes

# COATING THICKNESS GAUGE IPX-201F

