

7300 SERIES

HEAVY DUTY BENCH WEIGHING SCALES

Fast, Flexible, Dependable

Whether as a stand-alone scale or building block for a weight processing system, the 7300 series has what it takes to provide accurate weighings year after year. Rugged cast construction. High resolution electronics. Remote display connector. Four year warranty. Flexible RS-232 communications. Whatever you weigh, there's a 7300 series scale to exceed your expectations.

- ▲ AC/DC Power Option
- ▲ USB, Ethernet, Analog Communication
- ▲ Equipped for Remote Display



PENNSYLVANIA



Just Weigh The Difference

7300 SERIES

HEAVY DUTY BENCH WEIGHING SCALES

Features:

- Lbs and Kgs or any (2) weight units
- Standard RS-232 by DB9; USB option
- HD cast construction
- Large 12 x 14" platform (10lbs and >)
- NTEP; Canada COC
- HD industrial power cord
- Remote display connector standard
- Option AC/DC integrated functions like a UPS
- Powerful, flexible communications
- +Series universal main board/easy service
- Four Year Limited Warranty

Applications:

- Shipping manifest systems
- SPC/SQC or ingredient weighing
- Point-of-sale
- Animal or sample weighing

Weight Capacities:

Capacities and Accuracies, NTEP to 10,000 d.

2 x 0.0002 lb – 907.2 x 0.1 g*

5 x 0.0005 lb – 2268 x 0.2 g*

10 x 0.001 lb – 4536 x 0.5 g*

20 x 0.002 lb – 9.072 x 0.001 kg*

50 x 0.005 lb – 22.68 x 0.005 kg*

100 x 0.01 lb – 45.36 x 0.005 kg*

150 x 0.02 lb – 68.04 x 0.01 kg*

200 x 0.02 lb – 90.72 x 0.01 kg*

Platform Sizes

8" x 8" Aluminum

8" x 8" Aluminum

12" x 14" ss

12" x 14" ss

12" x 14" ss

12" x 14" ss

12" x 14" ss

12" x 14" ss

*(2) standard weight units can be provided as Primary and Secondary units of measure: Other weight units & resolutions including Lb/Oz – can be specified with order – consult factory.

NOTE: Not all custom units and resolutions are suitable for Commercial Applications

Display(s):

Stable, 0.56" high intensity red LED display

Buttons for ZERO, UNITS, PRINT

Up to (2) additional remote displays (option) connector provided

Option with/without internal display

Data Communication:

Bidirectional RS-232 standard, USB

Optional Ethernet output

Optional Analog 0-10 VDC/4-20 mA proportional output

Default settings for most manifesting systems

Custom software, outputs, features – contact factory

Compatible with serial printers for sheet, ticket, labels

Options:

AC/DC power, self-contained 30 hours+

Dual or Triple ranging resolution (specify) up to 20,000 stable divisions

Custom output strings

Remote display(s) – connector provided

PENNSYLVANIA

Authorized Distributor: